

Marmoleum voldoet aan de eisen van de norm ISO 24011/EN 548.

Marmoleum  
Ohmex

|                                                                                     |                      |                     |                                                |
|-------------------------------------------------------------------------------------|----------------------|---------------------|------------------------------------------------|
|    | ISO 24346 / EN 428   | 2,5 mm              |                                                |
|    | ISO 10874            | Klasse 23           |                                                |
|    | ISO 10874            | Klasse 34           |                                                |
|    | ISO 10874            | Klasse 42           |                                                |
|    | ISO 24341 / EN 426   | 2,00 m              |                                                |
|  | ISO 24341 / EN 426   | ≤ 32 m              |                                                |
|  | ISO 24343-1 / EN 433 | < 0,15 mm           |                                                |
|  | ISO 4918 / EN 425    | √                   |                                                |
|  | ISO 26987 / EN 423   | √                   |                                                |
|  | DIN 51130            | R9                  |                                                |
|  | EN ISO 717-2         | ≤ 5 dB              |                                                |
|  | EN 1081              | $1 \cdot 10^6 < R1$ | < $1 \cdot 10^8 \Omega$ - statisch dissipatief |

Marmoleum voldoet aan de eisen van de norm EN 14041



|                                                                                     |            |                     |  |
|-------------------------------------------------------------------------------------|------------|---------------------|--|
|  | EN 13501-1 | C <sub>fl</sub> -s1 |  |
|  | EN 13893   | DS: ≥ 0,30          |  |
|  | EN 1815    | < 2 kV              |  |
|  | EN 12524   | 0,17 W/m·K          |  |